Application No: 10/070,867 Attorney's Docket No: IT 010006

CLAIM AMENDMENTS

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims

1. (Currently Amended) A method of coding a data stream-(S1,S2), the method comprising: channel coding (11) respective partitions of a given part of the data stream with different error protection rates to obtain a coded data stream-(WS1, WS2); and

including (14, 20) a single length information (1f) field field concerning respective lengths of the respective partitions in the coded data stream (WS1, WS2).

- 2. (Currently Amended) The method as claimed in claim 1, wherein the length information (If) fieldfield includes the lengths of the partitions before channel coding.
- 3. (Currently Amended) The method as claimed in claim 1, wherein the length information—(If) field field includes the lengths of the partitions after channel coding.
- 4. (Currently Amended) The method as claimed in claim 1, wherein the length information (If) field is included after a resync marker (II5) of the given part of the data stream (S1, S2).
- 5. (Currently Amended) The method as claimed in claim 1, wherein the data stream (\$1, \$2) includes at least one marker (H1... H5) out of a predetermined set of at least two mutually different

P.08

Application No: 10/070,867 Attorney's Docket No: IT 010006

markers (H1... H5), the marker indicating a start of a given part of the data stream, the method further comprising:

representing (13) the at least one marker (H1... H5) with a higher robustness word (WH1... WH5) having a higher robustness to channel errors than the at least one marker; and outputting-(14) the data stream with the at least one marker represented with the higher-robustness word (WH)... WH5).

(Currently Amended) A method of decoding a coded data stream (WS1, WS2), in which 6. coded data stream respective partitions of a given part of the coded data stream have been channel encoded with different error protection rates, the coded data stream further includes a single length information-(1f) field field concerning respective lengths of the respective partitions in the coded data stream, the method comprising:

reading (40) the length information (11) field field; and channel decoding (31) the coded data stream (WS1, WS2) using the length information (19) field field to obtain a decoded data stream (S1, S2).

- (Currently Amended) The method as claimed in claim 6, further comprising: deleting (40, 31, 34) the length information (1f) field field from the coded data stream.
- (Currently Amended) An encoder for coding a data stream (\$1, \$2), the encoder comprising: 8.

P.09

Application No: 10/070,867 Attorney's Docket No: IT 010006

a channel encoder-(11) for channel coding respective partitions of a given part of the data stream with different error protection rates to obtain a coded data stream-(WS1, WS2); and means-(14, 20) for including a single length information-(1f) field field concerning respective lengths of the respective partitions in the coded data stream (WS1, WS2).

(Currently Amended) A decoder for decoding a coded data stream (WS1, WS2), in which 9. coded data stream respective partitions of a given part of the coded data stream have been channel encoded with different error protection rates, the coded data stream further including a single length information-(If) field field concerning respective lengths of the respective partitions in the coded data stream, the decoder comprising:

means (40) for reading the length information field; and means (31) for channel decoding the coded data stream (WS1, WS2) using the length information-(11) field field to obtain a decoded data stream (\$1, \$2).

(Currently Amended) A transmitter for transmitting a coded data stream (WS1, WS2), the 10. transmitter comprising:

an encoder for coding a data stream-(\$1, \$2), the encoder including

a channel encoder-(11) for channel coding respective partitions of a given part of the data stream with different error protection rates to obtain a coded data stream (WS1, WS2), and

Application No: 10/070,867

Attorney's Docket No: IT 010006

means (14, 20) for including a single length information (1f) field field concerning respective lengths of the respective partitions in the coded data stream (WS1, WS2); and means-(14) for transmitting the coded data stream-(WS1, WS2).

(Currently Amended) A receiver for receiving a coded data stream (WS1, WS2), the receiver 11. comprising:

means (30) for receiving the coded data stream; and

a decoder for decoding a coded data stream (WS1, WS2), in which coded data stream respective partitions of a given part of the coded data stream have been channel encoded with different error protection rates, the coded data stream further including a single length field information field concerning respective lengths of the respective partitions in the coded data stream, the decoder including

means (40) for reading the length information field field, and means (31) for channel decoding the coded data stream-(WS1, WS2) using the length information (1f) field field to obtain a decoded data stream (S1, S2).

12. (Currently Amended) A computer implemented coded data stream (WS1, WS2) in which respective partitions of a given part of the coded data stream have been channel encoded with different error protection rates, the coded data stream further comprising a single length information (11)-field field concerning respective lengths of the respective partitions in the coded data stream.

Application No: 10/070,867

Attorney's Docket No: IT 010006

13. (Currently Amended) A <u>computer implemented</u> storage medium—(15) on which a coded data stream—(WS1, WS2) has been stored, the coded data stream having respective partitions of a given part of the coded data stream have been channel encoded with different error protection rates, the coded data stream further comprising a single length information—(1f) field field concerning respective lengths of the respective partitions in the coded data stream.